

## **KPH 1500/1800/2100/2400 Wireless - Manual Supplement**

### **Wireless Operation Salus RT310 / RT510 7Day**

The KPH 1500/1800/2100/2400 wireless models includes a wireless receiver powered by internal mains supply and a wireless room stat powered by 2 x AA batteries (included)

For the thermostat operation please use the Salus Manual provided

The unit comes ready configured to use but in case it ever loses communication please push and hold the small black "sync" button through the access hole (RF SYNC) on the left side of the casing (See Photo Below) The red light above will start flashing until the ID of the thermostat is received. This will happen for a max of 12 minutes.

While receiver in "Sync" mode press and hold the Test/Pairing button (behind the sliding front door) on the thermostat for 3 seconds until the screen displays "SY9 or 10SY" this should pair the units and the red light should go out on the heater .

### **IT 500 Smart App Controllable Stat**

The thermostat is pre synchronised to the heater , remember on this model when you alter the temp set point up or down please press the tick button to confirm.

You will need to follow the supplied instructions from Salus for registering and operating your unit online and downloading the smart phone App.

Please select the heating configuration mode to system1 (one central heating zone only)

**Please note: All Wireless and App controlled thermostats will only control your plinth heater and not your central heating Boiler. Hot water must be flowing through heater before the fan will run.**

If you have any trouble please email [technical@thermix.co.uk](mailto:technical@thermix.co.uk)

