



Habanero - Models

Habanero 1800-C & Habanero 2100-C (Classic)
 Habanero 1800-W & Habanero 2100-W (Wireless)
 Habanero 1800-LV & Habanero 2100-LV (Low Voltage)
 Habanero 1800-WLV & Habanero 2100-WLV (LV Wireless)











Features:

- Perfect for domestic and commercial
- Rapid heat in small foot print
- Quieter operation
- Classic & Wireless models
- Low Voltage DC models
- Controllable via wireless room thermostat (wireless models only)
- Online controller (Optional for Wireless models) – *Control your Habanero from your smartphone*
- Integrated water temperature sensor

Habanero fan convectors provide warmth to the low levels of a room. The fan convectors are more energy efficient and effective than traditional panel radiators, as the Habanero fan convector gets the fan blowing the air gently into the room allowing the room to heat up quicker than traditional radiators.

The run time of the fan convector is lower than traditional radiators, heating the room faster, thereby reducing the boiler or heat pump run time and saving you energy.

Thermix proudly launched the innovative wireless range (patent pending). This gives better temperature control in areas where the heater is fitted. Now available in our low voltage DC option.

	DESIGNED AND MADE IN GREAT BRITAIN		APP CONTROLLABLE
	WIRELESS THERMOSTAT		2 SPEED FAN CONTROL
	COMPATIBLE WITH BOTH TRADITIONAL BOILERS AND HEAT PUMPS		ENERGY EFFICIENT COMPARED TO TRADITIONAL RADIATORS
	PEACE OF MIND WARRANTY		ULTRA LOW POWER DC FANS WITH CONSUMPTION UNDER 4 WATTS PER HOUR

Habanero 1800-C & Habanero 2100-C (Classic)

All of our Habanero hydronic can be integrated straight into your existing central heating system. We currently offer two models in the hydronic range providing outputs from 1.8 kW to 2.1 kW. Our classic models come with two speed option and integral water temperature switch to activate the heater when central heating system comes on.



Habanero 1800-W & Habanero 2100-W (Wireless)

Our Patent pending wireless models give better control of room temperature where the heater is fitted. The wireless thermostat allows you to set the desired room temperature and the heater will switch on/off automatically. All the other features are the same as our classic models (i.e. outputs, fan speeds, integral temperatures sensor and system integration).



Habanero 1800-LV & Habanero 2100-LV (Low Voltage)

With all the features that come with our classic models, our Low voltage models can be installed in high humidity areas such as bathrooms and en-suites. Two models in Hydronic low voltage range providing outputs of 1.8kW & 2.1kW. Our Low voltage models come a with simple on/off switch providing a single fan speed control and integral water temperature sensor to activate the heater when central heating system comes on. Our Ultra low power fans keep the power consumption under 4 watts/hour.



Habanero 1800-WLV & Habanero 2100-WLV (LV Wireless)

Our Patent pending wireless models give better control of room temperature where the heater is fitted. The wireless thermostat allows you to set the desired room temperature and the heater will switch on/off automatically.

All the other features are the same as our classic models (i.e. outputs, fan speeds, integral temperatures sensor and system integration).



CONTROLS AND ACCESSORIES

WIRELESS THERMOSTAT

These models are supplied with a wireless room thermostat to activate the heater unit depending on the room temperature.

Note: If you need to control multiple units with one wireless room thermostat please let us know at the time of ordering. We can reconfigure the receiver units within the heaters to take the command from one wireless thermostat.



OPTIONAL – APP CONTROLLED THERMOSTAT

All our wireless models can be supplied with App controllable thermostat. Please contact us for more info.



Technical Specifications

		Output @ 70°C (watts) (BTU)		Output @ 50°C (watts) (BTU)		Motor power (watts)		Pipes	Flexible hose	Wireless Thermostat
		Normal	Boost	Normal	Boost	Normal	Boost			
Habanero 1800-C	36m ³	1505 (5135)	1702 (5800)	738 (2520)	840 (2870)	15	19	15mm	Yes	No
Habanero 2100-C	45m ³	1669 (5700)	1861 (6350)	1039 (3545)	1270 (4330)	15	19	15mm	Yes	No
Habanero 1800-CW	36m ³	1505 (5135)	1702 (5800)	738 (2520)	840 (2870)	15	19	15mm	Yes	Yes
Habanero 2100-CW	45m ³	1669 (5700)	1861 (6350)	1039 (3545)	1270 (4330)	15	19	15mm	Yes	Yes
Habanero 1800-CLV	36m ³	1505 (5135)	N/A	738 (2520)	N/A	3.7	-	15mm	Yes	No
Habanero 2100-CLV	45m ³	1669 (5700)	N/A	1039 (3545)	N/A	3.7	-	15mm	Yes	No
Habanero 1800-CLVW	36m ³	1505 (5135)	N/A	738 (2520)	N/A	3.7	-	15mm	Yes	Yes
Habanero 2100-CLVW	45m ³	1669 (5700)	N/A	1039 (3545)	N/A	3.7	-	15mm	Yes	Yes

Dimensions: 440mm x 360mm x 95mm (W x H x D)

Note: All the heat outputs are tested in accordance with BS4856 using the entering water temperature and 340 l/h flow rate. Room size guide for guidance only based on the entering water temperature of 75°C.



DEALER STAMP

